



6

D

C

B

A

6

Adaptador M_SC a M_SC no continuo
Male SC Thread to Male SC Thread Non continuous Adapter

Rosca SC
Female SC Thread

Adaptador M_IS a M_IS
Male IS Thread to Male IS Thread Adapter

Rosca IS
Female IS Thread

Rosca IS
Female IS Thread

Barrilete 2.5" Rosca IS
2.5" Barrel IS Thread

Diámetro Máximo 212 mm
Maximun diameter 212 mm

Espesor 25 mm
Thickness 25 mm

Rosca IS equivalente a rosca 2" 9/16 24 UN - 2A
Thread IS equivalent to thread 2" 9/16 24 UN - 2A

Rosca SC equivalente a 2" 24 UN - 2A
Tnread SC equivalent to thread 2" 24 UN - 2A

∅12.00

Adaptad0o M_SC a M_M48
Male SC Thread to Male M48 Thread Adapter

Adaptador M_IS a F_SC
Male IS Thread to Female SC Thread Adapter

Rosca IS
Female IS Thread

Extensor M42 Continuo
Male M42 Thread Continous Extensor

25.00

Adaptador M_SC a F_M42
Male SC Thread to Female M42 Thread Adapter

Rosca SC
Female SC Thread

Rosca IS
Male IS Thread

Disponibles otros diámetros de Barrilete
Other Barrel diameter available too

Rotarion PRO High Load 4 ports with variable diameters
including TVO IS threads and 2,5 inch barrel

Diseño de FLAG	Revisado por	Aprobado por	Fecha	Fecha 07/05/2019
AstronSCIENTIFIC			RotarionCargaAlta4	
			Edición	Hoja 3 / 3

1

D

C

B

A

1

3

1

2

1

1

4

3

2

1

5

6

4

3

2

1

5

6